

## **Foundry Products Selection Guide**

		Engineered Sand Additives											Iron Oxides		Specialty Sands		
		Veinseal 14000	Veinseal 15000	Veinseal 18/41	Veinseal RB 30	Veinseal 135	Veinseal 581	Veinseal 11000	Veinseal 11250R	Veinseal 57	Veinseal 800	Veinseal 3000	BlackCAST	RedCAST	CeramCAST	ChromeCAST	ZirCAST
Resin Compatibility Casting Types Alloys %	Typical Addition Levels	2-10	2-10	2-10	2-7	2-7	0.5-2	0.5-3	0.5-3	2-4	2-4	5-20	3-5	1-3			
	Gray & Ductile Iron	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES		YES		
	Steel											YES	YES	YES	YES	YES	YES
	Non-Ferrous		YES				YES	YES	YES	YES	YES			YES	YES		
	Thin-Sectioned Automotive (<1")	YES		YES	YES	YES	YES	YES	YES	YES	YES			YES	YES		
	Medium-Sectioned Automotive (1"-3")	YES	YES	YES	YES	YES	YES			YES	YES			YES	YES		
	Heavy-Sectioned Iron (>3")		YES	YES			YES			YES	YES	YES	YES	YES	YES	YES	YES
	Thin & Heavy Sectioned Steel											YES	YES	YES	YES	YES	YES
	Thin & Heavy Sectioned Non-Ferrous		YES				YES	YES	YES	YES	YES		YES	YES	YES		
	Phenolic Urethane Cold Box	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
	Phenolic Urethane No-Bake	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
	Furan / Acid Setting	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
	Hot Box / Warm Box	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES			YES	YES		
	Esther-Cured Phenolic	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES	YES
	Resin Coated Sand (Shell Sand)	YES	YES	YES	YES	YES	YES			YES	YES		YES	YES	YES		

The information and recommendations contained herein are based on data we believe to be reliable and does not imply any warranty or performance guarantee, as conditions and methods of use of our products are beyond our control. The data herein is determined using Vibrantz's standard test methods. Hazard and safety information with respect to this product is available in the applicable SDS. Vibrantz will not be liable under any circumstance for consequential or incidental damages, including but not limited to, lost profits resulting from the use of our products.